

## BACKGROUND OF THE INVENTION

### FIELD OF THE INVENTION

The present invention relates generally to devices for preventing birds from landing or perching on selected surfaces, and more specifically to a bird repellent apparatus that comprises a base member and integral prongs preferably made out of injection molded plastic for simple and low cost manufacture and easy installation on virtually any surface to which access to birds is to be denied.

### PRIOR ART

The presence of birds on window sills, roof tops, boat masts and covers and the like is often undesirable. Bird droppings attract insects and provide a fertile bed for bacteria which can present a significant health hazard. Additionally, the unaesthetic appearance of bird droppings and the like often requires the task of unpleasant and time consuming clean up where access to the droppings is available. Often times the repulsive appearance of bird droppings and other by-products of birds is not even accessible for clean up.

The use of a plurality of pointed objects, such as spikes and the like, mounted on surfaces where it is desired to repel birds is not unknown. However, heretofore the typical bird repellent apparatus comprises a metal base having a plurality of angularly and upwardly projecting metal wires or spikes. Unfortunately, such metal contraptions, while accomplishing the desired result, tend to be costly to manufacture because they are not conducive to non-labor intensive manufacturing processes such as injection molding for example. Perhaps most importantly, they tend to be relatively expensive, which inherently limit their use.

1     There is a need therefore for a bird repellent apparatus which is easy and less costly  
2     to manufacture and which is relatively inexpensive to the user, thereby facilitating its  
3     use in larger numbers for avoiding the aforementioned problems of insect and bacteria  
4     infestation and unaesthetic appearance of the droppings and other waste products  
5     birds leave in their wake.

6  
7     Until the issuance of the applicant's prior patent, namely U.S. Patent No. 5,253,444,  
8     the typical bird repellent apparatus comprised a metal base having a plurality of  
9     angularly and upwardly projecting metal wires or spikes. Unfortunately, such metal  
10    contraptions, while accomplishing the desired result, tend to be costly to manufacture  
11    because they are not conducive to non-labor intensive manufacturing processes such  
12    as injection molding for example. Most importantly, they tend to be relatively  
13    expensive, which inherently limits their use. The disadvantages of such prior art was  
14    addressed in the applicant's prior disclosure in the aforementioned patent, relating to a  
15    bird repellent apparatus comprising a base member and a plurality of top members,  
16    each of which holds a plurality of prongs. All of the components of the applicant's prior  
17    invention can preferably be made of an injection molded plastic which can be cheaply  
18    manufactured in large numbers with virtually no significant labor costs. The use of  
19    injection molded plastics not only reduces the cost of manufacture and thus the cost to  
20    the user, but also provides the opportunity to manufacture the product in a variety of  
21    different colors, some of which may be selected to blend in with the color of the  
22    underlying surface and some of which may be purposely selected to provide an  
23    aesthetically pleasing and distinctive appearance. In any case, the applicant's prior  
24    invention provides an efficient, effective apparatus for repelling birds from surfaces,  
25    such as window sills, roof tops, boat masts, boat covers and the like, while overcoming  
26    the disadvantages of the prior art devices. However, the need for separate base  
27    members, top members and prongs, makes for a more costly apparatus because of the  
28    need for separate manufacture of the various components and assembly of such  
29    components. Moreover, that prior art configuration is inherently more difficult to install

1 and is inherently less durable because of having a plurality of separate components.  
2 Thus, there is a continuing need for a unitary apparatus which is easier to manufacture  
3 and install and which is more durable and lower in cost.

4

09347903 05499  
564250" EDCZTE60

## SUMMARY OF THE INVENTION

The aforementioned need is satisfied by the present invention which provides significant advantages over the aforementioned prior art. More specifically, the present invention comprises a bird repellent apparatus having an integral base member and a plurality of prongs preferably made of an injection molded plastic which can be cheaply manufactured in large numbers with virtually no significant labor costs. The base member, by means of a plurality of tabs having holes for receiving screws or other fasteners, can be affixed to virtually any desired surface. The plurality of prongs with sharp tips presents an impossible barrier to birds that would otherwise land or perch on the surface to which the present invention is affixed. The use of a unitary, integral injection molded plastic structure, not only reduces the manufacture cost and thus the cost to the user, but also provides the opportunity to manufacture the product in a variety of different colors, some of which may be selected to blend in with the color of the underlying surface and some of which may be purposely selected to provide an aesthetically pleasing and distinctive appearance. In either case, it can be seen that the present invention provides an efficient and effective apparatus for repelling birds from surfaces such as window sills, roof tops, boat masts and boat cover and the like, while overcoming the previously described disadvantages of the prior art.

## OBJECTS OF THE INVENTION

It is therefore a principal object of the present invention to provide a bird repellent apparatus for installation on selected surfaces for preventing birds from landing or perching thereon and which overcomes the disadvantages of the prior art.

It is an additional object of the present invention to provide a bird repellent apparatus made entirely of low cost plastic.

It is still an additional object of the present invention to provide a bird repellent apparatus of the type having a plurality of sharp-tipped prongs to prevent birds from landing or perching upon selected surfaces, the apparatus having an integral base member.

It is still an additional object of the present invention to provide a bird repellent apparatus comprising an injection molded or extruded plastic base member and a plurality of sharp-tipped prongs, the base member and prongs all being integrally formed to provide a unitary structure.

It is yet an additional object of the invention to provide a unitary plastic bird repellent apparatus having installation enhancement features including break point grooves for easy cutting, a glue trough for adhering the apparatus to hard surfaces and molded screw holes for attachment to wood surfaces and the like.

## BRIEF DESCRIPTION OF THE DRAWINGS

The aforementioned objects and advantages of the present invention, as well as additional objects and advantages thereof will be more fully understood hereinafter as a result of a detailed description of a preferred embodiment when taken in conjunction with the following drawings in which:

FIG. 1 is a three-dimensional illustration of the present invention shown ready for installation on an exterior window sill adjacent a window frame or other suitable surface;

FIG. 2 is a plan view of the present invention;

FIG. 3 is a side view of the present invention;

FIG. 4 is a cross-sectional view of the invention taken along lines 4-4 of FIG. 2; and

FIGs. 5, 6 and 7 are cross-sectional views of various elements of the invention taken along lines 5-5, 6-6 and 7-7 of FIG. 4.

## DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

Referring to FIGs. 1 and 2, it will be seen that the bird repellent apparatus 10 of the present invention comprises a base member 12 and a plurality of prongs 14. Each such prong terminates in a sharp tip 16. The base member 12 provides a rail 15 from which extends integrally therefrom the prongs 14 along the full length of base member 12. A plurality of flanges 18 each has a hole 20 and extends in opposed directions away from the rail 15. Each hole 20 is adapted to receive a screw for connecting the base member 12 to an underlying surface such as a window sill. A notch 19 provides a convenient cutting line at various locations along the base member 12 to permit length selection at the installation site.

The prongs 14 are provided at various angles relative to the underlying surface. As shown best in FIG. 3, prongs 22 are oriented at 90 degrees relative to the underlying surface, prongs 26 and 30 are oriented at about 30 degrees above the underlying surface and prongs 24 and 28 are oriented at about 70 degrees above the underlying surface. Moreover, prongs 26 and 30 are on opposed sides of the rail 15 as are prongs 24 and 28. As shown in FIGs. 1 and 2, this orientation of the prongs forms a repetitive pattern along the length of base member 12. As shown best in FIG. 3, a glue trough 17 permits neat glue application for installation on hard surfaces such as concrete brick and steel.

As shown in FIGs. 4-7, the cross-section of the prongs where they connect to rail 15 is "T"-shaped as shown in FIG. 5. The cross-section of the prongs along their major length is cross-shaped as shown in FIG. 6 and the cross-section of the prongs close to their pointed ends 16 is circular as shown in FIG. 7.

1 A key feature of the present invention is the unitary structure of the entire bird  
2 repellent apparatus shown in FIGs. 1 and 2. This feature permits the disclosed  
3 embodiment to be fabricated as a single injection-molded plastic member obviating any  
4 further assembly before installation on an underlying surface. This unique unitary  
5 design reduces fabrication costs and simplifies installation as well.

6  
7 Having thus disclosed an exemplary embodiment, it being understood that other  
8 configurations are contemplated as being within the scope hereof, what is claimed is:  
9

09317303 052499  
664250" 00E2FE60